



Aluminium- Vierkant- bzw. Rechteckrohre

warmausgehärtet, gepresst, AlMgSi0,5

Bezeichnung	Höhe (mm)	Breite (mm)	Stärke (mm)	Gewicht (kg/m)
20 x 10 x 2	20	10	2	0,291
20 x 15 x 2	20	15	2	0,350
25 x 10 x 2	25	10	2	0,340
25 x 15 x 2	25	15	2	0,414
25 x 20 x 2	25	20	2	0,440
30 x 10 x 1,5	30	10	1,5	0,300
30 x 15 x 2	30	15	2	0,443
30 x 20 x 2	30	20	2	0,497
30 x 20 x 3	30	20	3	0,734
34 x 20 x 2	34	20	2	0,540
35 x 15 x 2	35	15	2	0,515
35 x 25 x 2	35	25	2	0,660
40 x 15 x 2	40	15	2	0,571
40 x 20 x 2	40	20	2	0,605
40 x 20 x 2,5	40	20	2,5	0,743
40 x 20 x 3	40	20	3	0,875
40 x 30 x 2	40	30	2	0,734



Aluminium-Rechteckrohre werden nach EN 573-3 / 755-1,-2,-7,-9 gepresst hergestellt.

Güten:

AlMgSi 0,5 F22 (ENAW-6060 T6)

Handelslängen: ca. 6000 mm



Aluminium- Vierkant- bzw. Rechteckrohre

warmausgehärtet, gepresst, AlMgSi0,5

Bezeichnung	Höhe (mm)	Breite (mm)	Stärke (mm)	Gewicht (kg/m)
40 x 30 x 2,5	40	30	2,5	0,878
40 x 30 x 3	40	30	3	1,068
40 x 30 x 4	40	30	4	1,339
50 x 15 x 2	50	15	2	0,683
50 x 20 x 2	50	20	2	0,713
50 x 20 x 4	50	20	4	1,339
50 x 25 x 2	50	25	2	0,770
50 x 30 x 2	50	30	2	0,845
50 x 30 x 3	50	30	3	1,199
50 x 34 x 3	50	34	3	1,264
50 x 40 x 2	50	40	2	0,940
50 x 40 x 2,5	50	40	2,5	1,148
50 x 40 x 3	50	40	3	1,401
50 x 40 x 4	50	40	4	1,771
60 x 20 x 2	60	20	2	0,860
60 x 25 x 2	60	25	2	0,901
60 x 30 x 2	60	30	2	0,956



Aluminium- Vierkant- bzw. Rechteckrohre

warmausgehärtet, gepresst, AlMgSi0,5

Bezeichnung	Höhe (mm)	Breite (mm)	Stärke (mm)	Gewicht (kg/m)
60 x 30 x 3	60	30	3	1,361
60 x 34 x 3	60	34	3	1,426
60 x 40 x 2	60	40	2	1,040
60 x 40 x 2,5	60	40	2,5	1,283
60 x 40 x 3	60	40	3	1,523
60 x 40 x 4	60	40	4	1,987
60 x 50 x 3	60	50	3	1,685
70 x 20 x 2	70	20	2	0,963
70 x 40 x 3	70	40	3	1,735
80 x 20 x 2	80	20	2	1,040
80 x 25 x 2	80	25	2	1,123
80 x 30 x 3	80	30	3	1,683
80 x 40 x 2	80	40	2	1,270
80 x 40 x 3	80	40	3	1,847
80 x 40 x 4	80	40	4	2,419
80 x 50 x 2	80	50	2	1,360
80 x 50 x 4	80	50	4	2,635



Aluminium- Vierkant- bzw. Rechteckrohre

warmausgehärtet, gepresst, AlMgSi0,5

Bezeichnung	Höhe (mm)	Breite (mm)	Stärke (mm)	Gewicht (kg/m)
80 x 60 x 3	80	60	3	2,170
80 x 60 x 4	80	60	4	2,850
100 x 18 x 2	100	18	2	1,231
100 x 20 x 2	100	20	2	1,290
100 x 25 x 2	100	25	2	1,310
100 x 30 x 2	100	30	2	1,370
100 x 30 x 3	100	30	3	2,009
100 x 40 x 2	100	40	2	1,470
100 x 40 x 3	100	40	3	2,170
100 x 40 x 4	100	40	4	2,851
100 x 50 x 2	100	50	2	1,580
100 x 50 x 3	100	50	3	2,330
100 x 50 x 4	100	50	4	3,067
100 x 60 x 2	100	60	2	1,735
100 x 60 x 4	100	60	4	3,290
100 x 80 x 3	100	80	3	2,820
120 x 20 x 2	120	20	2	1,512



Aluminium- Vierkant- bzw. Rechteckrohre

warmausgehärtet, gepresst, AlMgSi0,5

Bezeichnung	Höhe (mm)	Breite (mm)	Stärke (mm)	Gewicht (kg/m)
120 x 30 x 2	120	30	2	1,624
120 x 40 x 2,5	120	40	2,5	2,155
120 x 40 x 3	120	40	3	2,511
120 x 40 x 4	120	40	4	3,283
120 x 50 x 4	120	50	4	3,499
120 x 60 x 3	120	60	3	2,820
120 x 60 x 4	120	60	4	3,800
120 x 80 x 3	120	80	3	3,310
140 x 40 x 4	140	40	4	3,710
140 x 80 x 4	140	80	4	4,580
150 x 40 x 4	150	40	4	3,931
150 x 50 x 4	150	50	4	4,147
180 x 50 x 4	180	50	4	4,957
200 x 50 x 2,5	200	50	2,5	3,375
200 x 50 x 4	200	50	4	5,227
200 x 100 x 4	200	100	4	6,541