



## T-Stahl

rundkantig

DIN EN 10055

| Bezeichnung<br>T-Stahl | Höhe<br>(mm) | Breite<br>(mm) | Dicke<br>(mm) | Gewicht<br>(kg/m) |
|------------------------|--------------|----------------|---------------|-------------------|
| T 20                   | 20           | 20             | 3,0           | 0,880             |
| T 25                   | 25           | 25             | 3,5           | 1,290             |
| T 30                   | 30           | 30             | 4,0           | 1,770             |
| T 35                   | 35           | 35             | 4,5           | 2,330             |
| T 40                   | 40           | 40             | 5,0           | 2,960             |
| T 45                   | 45           | 45             | 5,5           | 3,670             |
| T 50                   | 50           | 50             | 6,0           | 4,440             |
| T 60                   | 60           | 60             | 7,0           | 6,230             |
| T 70                   | 70           | 70             | 8,0           | 8,320             |
| T 80                   | 80           | 80             | 9,0           | 10,700            |
| T 90                   | 90           | 90             | 10,0          | 13,400            |
| T 100                  | 100          | 100            | 11,0          | 16,400            |
| T 120                  | 120          | 120            | 13,0          | 23,200            |
| T 140                  | 140          | 140            | 15,0          | 31,300            |
|                        |              |                |               |                   |
|                        |              |                |               |                   |

